

Tow and Recovery vehicles • Construction vehicles • Utility vehicles • DOT and Municipal vehicles

FEATURES

- Advanced Solaris™ LED reflective light technology
- Stylish single-and-dual head models
- Functional push button synchronize and pattern control
- Choice of cigarette plug and synchronized designs
- New/Innovative warning patterns built-in
- Full variety of high intensity LED colors to choose from
- Versatile mounting brackets and snap-on flash guards included
- Extremely low amp draw
- Quietly meets EMI and RFI requirements

available in: 



ORDER INFORMATION

- | | |
|------------------|---|
| 329000-X | Single head (8 LEDs), 23 patterns, cigarette plug |
| 329001-X | Single head (8 LEDs), 23 patterns, 2P Sync |
| 329000-XX | Dual head (16 LEDs), 25 patterns, cigarette plug |
| 329001-XX | Dual head (16 LEDs), 25 patterns, 2P Sync |

	SINGLE UNIT	DUAL UNIT
SPECIFICATIONS		
Volts	12.8 VDC	
Current Draw	1.5A	2.2A
Operating Temp	-30°C to +65°C	
SHIP WEIGHT		
	1.0 lb (.45 kg)	1.5 lb (.68 kg)
DIMENSIONS		
Length	2.9 in (74 mm)	2.9 in (74 mm)
Width	4.3 in (109 mm)	8.5 in (216 mm)
Height	1.2 in (30 mm)	1.2 in (30 mm)

